TOSHIBA CMOS Digital Integrated Circuit Silicon Monolithic

TC4S584F


1. Function Functional Description

Schmitt Trigger

2. General

TC4S584F is the one circuit inverter having the Schmitt trigger function at the input terminal.
That is, since the circuit threshold level voltage at the leading and trailing edges of input waveform are different (VP, VN), the TC4S584F can be used in the broad range applications, including line receivers, waveform shaping circuit, astable multivibrators, and monostable multivibrators.


3. Packaging




SSOP5-P-0.95

Weight : 0.016 g (typ.)


4. Marking and Pin Assignment





(Top View)

5. Logic Diagram



Start of commercial production
1988-05

© 1988-2026
Toshiba Electronic Devices & Storage Corporation

6. Absolute Maximum Ratings (Ta = 25 °C) (Note)

Characteristics	Symbol	Rating	Unit
DC supply voltage	V_{DD}	V_{SS} − 0.5 to V_{SS} + 20	V
Input voltage	V_{IN}	V_{SS} − 0.5 to V_{DD} + 0.5	V
Output voltage	V_{OUT}	V_{SS} − 0.5 to V_{DD} + 0.5	V
DC input current	I_{IN}	±10	mA
Power dissipation	P_D	200	mW
Operating temperature range	T_{opr}	−40 to 85	°C
Storage temperature range	T_{stg}	−65 to 150	°C
Lead temperature (10 s)	T_L	260	°C

Note: Exceeding any of the absolute maximum ratings, even briefly, lead to deterioration in IC performance or even destruction.
Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.
Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

7. Operating Ranges (V_{SS} = 0 V)

Characteristics	Symbol	Test Condition	Min	Typ.	Max	Unit
DC supply voltage	V_{DD}	—	3	—	18	V
Input voltage	V_{IN}	—	0	—	V_{DD}	V

© 1988-2026
Toshiba Electronic Devices & Storage Corporation

8. Static Electrical Characteristics (V_{SS} = 0 V)

Characteristics	Symbol	Test Condition		V_{DD} (V)	−40°C Min	−40°C Max	25°C Min	25°C Typ.	25°C Max	85°C Min	85°C Max	Unit
High-level output voltage	V_{OH}	$\|I_{OUT}\|$ < 1 μA V_{IN} = V_{SS}		5 10 15	4.95 9.95 14.95	— — —	4.95 9.95 14.95	5.00 10.00 15.00	— — —	4.95 9.95 14.95	— — —	V
Low-level output voltage	V_{OL}	$\|I_{OUT}\|$ < 1 μA V_{IN} = V_{DD}		5 10 15	— — —	0.05 0.05 0.05	— — —	0 0 0	0.05 0.05 0.05	— — —	0.05 0.05 0.05	V
Output high current	I_{OH}	V_{IN} = V_{SS}	V_{OH} = 4.6 V V_{OH} = 2.5 V V_{OH} = 9.5 V V_{OH} = 13.5 V	5 5 10 15	−0.61 −2.5 −1.5 −4.0	— — — —	−0.51 −2.1 −1.3 −3.4	−1.0 −4.0 −2.2 −9.0	— — — —	−0.42 −1.7 −1.1 −2.8	— — — —	mA
Output low current	I_{OL}	V_{IN} = V_{DD}	V_{OL} = 0.4 V V_{OL} = 0.5 V V_{OL} = 1.5 V	5 10 15	0.61 1.5 4.0	— — —	0.51 1.3 3.4	1.5 3.8 15.0	— — —	0.42 1.1 2.8	— — —	mA
Positive trigger threshold voltage*	V_P	V_{OUT} = 0.5 V V_{OUT} = 1.0 V V_{OUT} = 1.5 V		5 10 15	1.95 4.3 6.9	3.65 7.1 10.7	2.05 4.5 7.1	2.9 5.9 9.0	3.35 7.1 10.6	2.05 4.7 7.1	3.75 7.2 10.8	V
Negative trigger threshold voltage*	V_N	V_{OUT} = 4.5 V V_{OUT} = 9.0 V V_{OUT} = 13.5 V		5 10 15	1.05 2.1 3.2	2.75 4.9 7.0	1.1 2.2 3.3	2.1 3.5 5.0	2.6 4.7 6.8	0.95 2.0 3.1	2.65 4.8 6.9	V
Hysteresis voltage*	V_H	—		5 10 15	0.1 1.7 3.1	1.35 3.2 4.8	0.4 1.8 3.2	0.75 2.4 4.0	1.3 3.2 4.8	0.4 1.7 3.2	1.50 3.4 4.9	V
Input current	“H” level	I_{IH}	V_{IH} = 18 V	18	—	0.1	—	10^{-5}	0.1	—	1.0	μA
	“L” level	I_{IL}	V_{IL} = 0 V	18	—	−0.1	—	-10^{-5}	−0.1	—	−1.0	
Quiescent supply current		I_{DD}	V_{IN} = V_{SS}, V_{DD}	5 10 15	— — —	1 2 4	— — —	0.001 0.002 0.004	1 2 4	— — —	7.5 15.0 30.0	μA

Note: Values are different to TC4584BP, TC4584BF marked* (V_P, V_N, V_H).


© 1988-2026
Toshiba Electronic Devices & Storage Corporation

9. Switching Characteristics (Ta = 25°C, V_{SS} = 0 V, C_L = 50 pF)

Characteristics	Symbol	Test Condition	V_{DD} (V)	Min	Typ.	Max	Unit
Output transition time	t_{TLH} t_{THL}	—	5 10 15	— — —	80 50 40	200 100 80	ns
Propagation delay time	t_{pLH} t_{pHL}	—	5 10 15	— — —	170 80 60	340 160 120	ns
Input capacitance	C_{IN}	—		—	5	7.5	pF


10. Circuit and Waveform for Measurement of Dynamic Characteristics

Circuit




P.G. : PULSE GENERATOR


Waveform



11. Input-Output Voltage Characteristics



・ Input-Output Voltage waveform




・ Transfer characteristics

© 1988-2026
Toshiba Electronic Devices & Storage Corporation

12. Package Dimensions

SSOP5-P-0.95 Unit : mm



Weight: 0.016 g (typ.)

© 1988-2026
Toshiba Electronic Devices & Storage Corporation

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as “TOSHIBA”.
Hardware, software and systems described in this document are collectively referred to as “Product”.

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, Class 3 medical devices, equipment used for automobiles, and military vehicles and munitions. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

© 1988-2026
Toshiba Electronic Devices & Storage Corporation