TOSHIBA PHOTOCOUPLER IRED & PHOTO-IC

TLP2418

PDP (Plasma Display Panel)

FA (Factory Automation)

Interfaces of measuring and control instruments

Operate at high ambient temperatures up to 125°C

Unit: mm



JEDEC	—
JEITA	—
TOSHIBA	11−5K1S

Weight: 0.11 g (typ.)

The Toshiba TLP2418 consists of an infrared emitting diode and integrated high-gain, high-speed photodetector.
The TLP2418 is housed in the SO8 package. The output stage is an open collector type.
The photodetector has an internal Faraday shield that provides a guaranteed common-mode transient immunity of ±15 kV/μs.

- Inverter logic type (Open collector output)
- Package: SO8
- Guaranteed performance over: -40 to 125°C
- Power supply voltage: 4.5 to 5.5 V
- Input threshold current: I_{FHL} = 5.0 mA (max)
- Propagation delay time t_{pHL}/t_{pLH}: 75 ns (max)
- Common-mode transient immunity: ±15 kV/μs (min)
- Isolation voltage: 3750 Vrms (min)
- UL-recognized: UL 1577, File No.E67349
- cUL-recognized: CSA Component Acceptance Service No.5A File No.E67349
- VDE-approved: EN 60747-5-5 (Note 1)
- CQC-approved: GB4943.1,GB8898 Japan Factory

仅适用于海拔 2000m 以下地区安全使用

Note 1 : When a VDE approved type is needed, please designate the **Option (V4)**.

Truth Table

Input	LED	Output
H	ON	L
L	OFF	H

Pin Configuration (Top View)



1:N.C.
2:ANODE
3:CATHODE
4: N.C.
5:GND
6:VO(Output)
7: N.C.
8:VCC

Schematic



A bypass capacitor of 0.1μF must be connected between pins 5 and 8.

Start of commercial production
2009-11

Not Recommended for New Design

Absolute Maximum Ratings (Ta=25°C)

Characteristic		Symbol	Rating	Unit
LED	Forward Current	I_F	25	mA
	Forward Current Derating (Ta ≥ 110°C)	ΔI_F /°C	-0.67	mA/°C
	Peak Transient Forward Current (Note 1)	I_{FPT}	50	mA
	Peak Transient Forward Current Derating (Ta ≥ 110°C)	ΔI_{FPT} /°C	-1.34	mA/°C
	Reverse Voltage	V_R	5	V
	Input Power Dissipation	P_D	40	mW
	Input Power Dissipation Derating (Ta ≥ 110°C)	ΔP_D /°C	-1.08	mW/°C
Detector	Output Current (Ta ≤ 125°C)	I_O	25	mA
	Output Voltage	V_O	6	V
	Supply Voltage	V_{CC}	6	V
	Output Power Dissipation	P_O	80	mW
	Output Power Dissipation Derating (Ta ≥ 110°C)	ΔP_O /°C	-2.0	mW/°C
Operating Temperature Range		T_{opr}	-40 to 125	°C
Storage Temperature Range		T_{stg}	-55 to 150	°C
Lead Soldering Temperature (10 s)		T_{sol}	260	°C
Isolation Voltage (AC, 60 s, R.H. ≤ 60 %) (Note 2)		BV_S	3750	V_{rms}

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings. Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note 1: Pulse width ≤ 1 ms, duty = 50 %.

Note 2: This device is regarded as a two terminal device: pins 1, 2, 3 and 4 are shorted together, as are pins 5, 6, 7 and 8.

Recommended Operating Conditions

Characteristic	Symbol	Min	Typ.	Max	Unit
Input Current, High Level	I_{FH}	7.5	—	15	mA
Input Voltage, Low Level	V_{FL}	0	—	0.8	V
Supply Voltage*	V_{CC}	4.5	—	5.5	V
Operating Temperature	T_{opr}	-40	—	125	°C

* This item denotes operating range, not meaning of recommended operating conditions.

Note: Recommended operating conditions are given as a design guideline to obtain expected performance of the device. Additionally, each item is an independent guideline respectively. In developing designs using this product, please confirm specified characteristics shown in this document.

Not Recommended for New Design

Electrical Characteristics
(Unless otherwise specified, Ta=-40 to 125°C, V_{CC}=4.5 to 5.5 V)

Characteristic	Symbol	Test Circuit	Test Condition	Min	Typ.	Max	Unit
Input Forward Voltage	V_F	-	I_F = 10 mA, Ta = 25 °C	1.40	1.57	1.80	V
Temperature Coefficient of Forward Voltage	$\Delta V_F/\Delta Ta$	-	I_F = 10 mA	-	-1.8	-	mV/°C
Input Reverse Current	I_R	-	V_R = 5 V, Ta = 25 °C	-	-	10	μA
Input Capacitance	C_T	-	V = 0 V, f = 1 MHz, Ta = 25 °C	-	60	-	pF
Logic High Output Current	I_{OH}	1	V_F = 0.8 V, V_O = 5.5 V	-	-	250	μA
			Ta = 25 °C	-	0.5	10	
Logic Low Output Voltage	V_{OL}	2	I_F = 10 mA, I_O = 13 mA (Sinking)	-	0.2	0.6	V
Logic Low Supply Current	I_{CCL}	3	I_F = 10 mA	-	1.5	5	mA
Logic High Supply Current	I_{CCH}	4	I_F = 0 mA	-	1.5	5	mA
"H Level Output to L Level Output" Input Current	I_{FHL}	-	I_O = 13 mA (Sinking), V_O < 0.6 V	-	1.0	5.0	mA

*All typical values are at Ta=25°C, V_{CC}=5 V unless otherwise specified

Isolation Characteristics (Ta = 25°C)

Characteristic	Symbol	Test Condition	Min	Typ.	Max	Unit
Capacitance input to output	C_S	V_S = 0 V,f = 1 MHz (Note 2)	—	0.8	—	pF
Isolation resistance	R_S	R.H. ≤ 60 %,V_S = 500 V (Note 2)	1×10^{12}	10^{14}	—	Ω
Isolation voltage	BV_S	AC, 60 s (Note 2)	3750	—	—	V_{rms}

Not Recommended for New Design

Switching Characteristics

(Unless otherwise specified, Ta=-40 to 125 °C, V_{CC}=4.5 to 5.5V)

Characteristic	Symbol	Test Circuit	Test Condition		Min	Typ.	Max	Unit
Propagation delay time (H→L)	t_{pHL}	5	I_F = 0→7.5 mA	R_L = 350 Ω, C_L = 15 pF (Note 4)	-	30	75	ns
Propagation delay time (L→H)	t_{pLH}		I_F = 7.5→0 mA		-	35	75	ns
Switching Time Dispersion between ON and OFF	$\|t_{pHL}-t_{pLH}\|$		I_F = 0⇄7.5 mA	R_L = 350 Ω, C_L = 15 pF (Note 4)	-	-	35	ns
Propagation Delay Skew (Note 5)	t_{psk}				-50	-	50	ns
Fall Time (90 – 10 %)	t_f		I_F = 0→7.5 mA	R_L = 350 Ω, C_L = 15 pF (Note 4)	-	30	-	ns
Rise Time (10 – 90 %)	t_r		I_F = 7.5→0 mA		-	30	-	ns
Common Mode transient Immunity at High Level Output	CM_H	6	V_{CM} = 1000 V_{p-p}, I_F = 0 mA, V_{CC} = 5 V, Ta = 25 °C		15	-	-	kV/μs
Common Mode transient Immunity at Low Level Output	CM_L		V_{CM} = 1000 V_{p-p}, I_F = 10 mA, V_{CC} = 5 V, Ta = 25 °C		-15	-	-	kV/μs

*All typical values are at Ta = 25 °C

Note 3: A ceramic capacitor (0.1 μF) should be connected from pin 8 (V_{CC}) to pin 5 (GND) to stabilize the operation of the high gain linear amplifier. Failure to provide the bypass may impair the switching property. The total lead length between capacitor and coupler should not exceed 1 cm.

Note 4: f = 5 MHz, duty = 50 %, input current t_r = t_f = less than 5 ns, C_L is approximately 15 pF which includes probe and Jig/stray wiring capacitance.

Note 5: Propagation delay skew is defined as the difference between the largest and smallest propagation delay times (i.e. t_{pHL} or t_{pLH}) of multiple samples. Evaluations of these samples are conducted under identical test conditions (supply voltage, input current, temperature, etc).

TEST CIRCUIT 1: I_{OH} Test Circuit



TEST CIRCUIT 2: V_{OL} Test Circuit



TEST CIRCUIT 3: I_{CCL} Test Circuit



TEST CIRCUIT 4: I_{CCH} Test Circuit



Not Recommended for New Design

TEST CIRCUIT 5: Switching Time Test Circuit

I_F = 7.5mA(P.G.)
(f = 5MHz , duty = 50%, tr = tf = less than 5ns)





C_L includes probe and stray capacitance.
P.G.: Pulse generator

TEST CIRCUIT 6: Common-Mode Transient Immunity Test Circuit





$$CM_H = \frac{800(V)}{t_f(\mu s)} \qquad CM_L = \frac{800(V)}{t_r(\mu s)}$$

Not Recommended for New Design

$I_F - V_F$



$I_F - T_a$



$V_{OL} - T_a$



$V_O - I_F$



$I_{FHL} - T_a$



$I_{CCH}, I_{CCL} - T_a$



NOTE: The above characteristics curves are presented for reference only and not guaranteed by production test, unless otherwise noted.

Not Recommended for New Design









NOTE: The above characteristics curves are presented for reference only and not guaranteed by production test, unless otherwise noted.

Not Recommended for New Design

PRECAUTIONS OF SURFACE MOUNTING TYPE PHOTOCOUPLER SOLDERING & GENERAL STORAGE

(1) Precautions for Soldering

1) When Using Soldering Reflow

- An example of a temperature profile when Sn-Pb eutectic solder is used:



This profile is based on the device's maximum heat resistance guaranteed value.
Set the preheat temperature/heating temperature to the optimum temperature corresponding to the solder paste type used by the customer within the described profile.

- An example of a temperature profile when lead(Pb)-free solder is used:



This profile is based on the device's maximum heat resistance guaranteed value.
Set the preheat temperature/heating temperature to the optimum temperature corresponding to the solder paste type used by the customer within the described profile.

- Reflow soldering must be performed once or twice.
- The mounting should be completed with the interval from the first to the last mountings being 2 weeks.

2) When using soldering Flow (Applicable to both eutectic solder and Lead(Pb)-Free solder)

- Apply preheating of 150 °C for 60 to 120 seconds.
- Mounting condition of 260 °C or less within 10 seconds is recommended.
- Flow soldering must be performed once

3) When using soldering Iron (Applicable to both eutectic solder and Lead(Pb)-Free solder)

- Complete soldering within 10 seconds for lead temperature not exceeding 260 °C or within 3 seconds not exceeding 350 °C .
- Heating by soldering iron must be only once per 1 lead

Not Recommended for New Design

(2) Precautions for General Storage

1) Do not store devices at any place where they will be exposed to moisture or direct sunlight.

2) When transportation or storage of devices, follow the cautions indicated on the carton box.

3) The storage area temperature should be kept within a temperature range of 5 °C to 35 °C, and relative humidity should be maintained at between 45% and 75%.

4) Do not store devices in the presence of harmful (especially corrosive)gases, or in dusty conditions.

5) Use storage areas where there is minimal temperature fluctuation. Because rapid temperature changes can cause condensation to occur on stored devices, resulting in lead oxidation or corrosion, as a result, the solderability of the leads will be degraded.

6) When repacking devices, use anti-static containers.

7) Do not apply any external force or load directly to devices while they are in storage.

8) If devices have been stored for more than two years, even though the above conditions have been followed, it is recommended that solderability of them should be tested before they are used.

Not Recommended for New Design

© 2019
Toshiba Electronic Devices & Storage Corporation

Specification for Embossed–Tape Packing (TP) for SO8 Coupler

1. Applicable Package

Package	Product Type
SO8	Photocoupler

2. Product Naming System

Type of package used for shipment is denoted by a symbol suffix after a product number. The method of classification is as below.

(Example)

TLP2418 (TP)

Tape type

Device name

3. Tape Dimensions

3.1 Orientation of Device in Relation to Direction of Tape Movement

Device orientation in the recesses is as shown in Figure 1.



Figure 1 Device Orientation

3.2 Tape Packing Quantity: 2500 devices per reel

3.3 Empty Device Recesses Are as Shown in Table 1.

Table 1 Empty Device Recesses

	Standard	Remarks
Occurrences of 2 or more successive empty device recesses	0 device	Within any given 40-mm section of tape, not including leader and trailer
Single empty device recesses	6 devices (max) per reel	Not including leader and trailer

3.4 Start and End of Tape

The start of the tape has 50 or more empty holes. The end of tape has 50 or more empty holes and two empty turns only for a cover tape.

Not Recommended for New Design

3.5 Tape Specification

(1) Tape material: Plastic (protection against electrostatics)

(2) Dimensions: The tape dimensions are as shown in Figure 2 and table 2.



Figure 2 Tape Forms

Table 2 Tape Dimensions

Unit: mm
Unless otherwise specified: ±0.1

Symbol	Dimension	Remark
A	6.5	—
B	5.6	—
D	5.5	Center line of indented square hole and sprocket hole
E	1.75	Distance between tape edge and hole center
F	8.0	Cumulative error $^{+0.1}_{-0.3}$ (max) per 10 feed holes
G	4.0	Cumulative error $^{+0.1}_{-0.3}$ (max) per 10 feed holes
K_0	3.1	Internal space

Not Recommended for New Design

3.6 Reel

(1) Material: Plastic

(2) Dimensions: The reel dimensions are as shown in Figure 3 and Table 3.



Figure 3 Reel Form

Table 3 Reel Dimensions

Unit: mm

Symbol	Dimension
A	Φ330 ±2
B	Φ80 ±1
C	Φ13 ±0.5
E	2.0 ±0.5
U	4.0 ±0.5
W1	13.5 ±0.5
W2	17.5 ±1.0

4. Packing

Packed in a shipping carton.

5. Label Indication

The carton bears a label indicating the product number, the symbol representing classification of standard, the quantity, the lot number and the Toshiba company name.

6. Ordering Method

When placing an order, please specify the product number, the tape type and the quantity as shown in the following example.

(Example)



Not Recommended for New Design

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as “TOSHIBA”.
Hardware, software and systems described in this document are collectively referred to as “Product”.

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, lifesaving and/or life supporting medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, and devices related to power plant. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- GaAs (Gallium Arsenide) is used in Product. GaAs is harmful to humans if consumed or absorbed, whether in the form of dust or vapor. Handle with care and do not break, cut, crush, grind, dissolve chemically or otherwise expose GaAs in Product.
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

Not Recommended for New Design

© 2019
Toshiba Electronic Devices & Storage Corporation